

# HANDHELD SCANNER

- Product availability and specifications depend on territory market strategy; all are subjects to change without prior notice.
- ZEBEX is the trademark of ZEBEX INDUSTRIES INC, all rights reserved.



## Z-3151HS

### Advanced Handheld High-Speed Laser Scanner

The Z-3151HS is a high class handheld single-line laser scanner with a powerful scan engine. It utilized the omnidirectional technology to transform seven laser lines into one and performs a superb scanning speed at 500 scans per second. The built-in Z-SCAN+ decoding technology guarantees real-time scanning and accuracy, ensuring an unbeatable first read success rate. The 32-bit MPU allows it to read most 1D barcode types, GS1 DataBar and PDF417.

- Decode most 1D barcodes, incl. GS1 DataBar & PDF 417
- Superb scanning ability
- Proprietary Z-SCAN+ technology
- Rugged and ergonomic form factor
- Flexible communications
- Honored by **IF Product Design Award 2009**



#### OPERATIONAL

Light Source	650 nm visible laser diode (VLD)
Microprocessor	32 bit
Depth of Field	35 – 200 mm (UPC/EAN 100%, PCS=90%)
Scan Angle	52°
Scan Rate	500 scans per second
Pitch/Roll/Skew Angle	65° / 30° / 65°
Minimum Bar Width	5 mil @ PCS=90% (Code 39)
Print Contrast	30% @ UPC/EAN 100%
Indicator	Three-color LED (green, red & blue)
Beeper Operation	Programmable tone & beep time
System Interface	Keyboard, RS-232, HID USB, USB Virtual COM, wand, OPOS, JPOS

#### PHYSICAL

Dimension	106.7 × 58.0 × 155.0 mm (device only)
Weight	148 g (stand excluded)
Cable	Standard 2M straight

#### POWER

Input Voltage	5 VDC ±10%
Operating Current	250 mA
Power Consumption	1.25 watts

#### REGULATORY

Laser Class	CDRH Class IIa; IEC 60825-1: Class 1
EMC	CE & FCC DOC compliance, VCCI, BSMI

#### ENVIRONMENTAL

Operating Temperature	0°C – 40°C (32°F – 104°F)
Storage Temperature	-20°C – 60°C (-4°F – 140°F)
Humidity	5% – 95% RH (non-condensing)
Light Level	4,500 Lux (fluorescence)
Drop Durability	Designed to withstand 1M drops

#### DECODING CAPABILITY

1D Barcode	UPC/EAN/JAN, UPC-A & UPC-E, EAN-8 & EAN-13, JAN-8 & JAN-13, ISBN/ISSN, Code 39, Codabar, Code 128 & EAN 128, Code 93, ITF, Addendum 2 of 5, IATA Code, MSI/Plessey, China Postal Code, Code 32, Industrial 2 of 5, Standard 2 of 5, DTF, JAP, Code 11, RSS 14, RSS Limited, RSS Expanded, Telepen
2D Barcode	PDF417



1. Clear LED indicators
2. Small footprint stands
3. Svelte shaped with solid housing

